



ALN-9627 “H” Inlay

The Alien Technology® ALN-9627 “H” RFID inlay is a general purpose inlay for small tickets and hang tags.



Powered by Alien®’s break-through **Higgs™3** UHF RFID IC and innovative “H” antenna design, the ALN-9627 delivers industry leading EPC Gen 2 performance in a form factor suitable for **small vertical labels and hang tags**, which makes it ideal for apparel and small label applications.

With its Higgs-3 core, the “H” delivers excellent performance and a rich feature set expanding the standard 32-bit TID with an **additional 64-bit Unique TID for authentication** and serialization applications, an **extensible EPC memory bank, 512-bits of user memory** for distributed data applications and **password protected read and write support capabilities** to prevent unauthorized viewing and modification of the tag’s data.

ALN-9627 inlays are *World Tag* compliant, enabling consistent operation across the diverse frequencies of the Americas, Europe, Middle East, Asia, and Africa.

Typical applications for the “H” include, but are not limited to:

- apparel, hang tags
- corrugate cases
- small package labels
- shipping labels
- asset management
- file folder labels


FEATURES

- Exceptional performance
- EPC Gen 2 (v1.2.0) compliant
- ISO/IEC 18000-6C compliant
- Worldwide RFID UHF operation (840-960MHz)
- Higgs™-3 IC with 800-bits of Nonvolatile Memory
 - 32-bit TID
 - 64-bit Unique TID
 - 96-bit EPC Memory, extensible to 480-bits
 - 512-bit User Memory
 - 32-bit Access password
 - 32-bit Kill password
- Pre-programmed with a unique, unalterable 64-bit serial number (ideal for authentication)
- User Memory can be Block Perma-Locked
- User Memory can be Read Password protected in 64-bit blocks, prohibiting unintended Reads without an access password
- Supports all Mandatory and Optional Gen 2 commands including item level commands
- Custom commands for high speed programming
- Available in high-yield, high-capacity dry/wet inlay rolls for high volume converting processes




ALN-9627 “H” Inlay

ALN-9627 Inlay Orientation




ALN-9627-FSR
(Dry Unslit Roll)




ALN-9627-FWRW
(White Wet Roll)

Standard Alien Inlay rolls unwind with metal antenna side facing outward with respect to the core.

ALN-9627 Inlay Specification



ALN-9627-FSR
(Dry Unslit Inlay)



ALN-9627-FWRW
(White Wet Inlay)



ALN-9627 “H” Inlay

ALN-9627 Inlay Stackup

DRY INLAY THICKNESS, $\pm 10\%$	
OVER ANTENNA	0.05 mm
OVER CHIP	0.25 mm

WHITE WET INLAY THICKNESS, $\pm 10\%$	
OVER ANTENNA	0.16 mm
OVER CHIP	0.36 mm




ALN-9627-FSR
(Dry Unslit Inlay)




ALN-9627-FWRW
(White Wet Inlay)

ALN-9627 Inlay Angular Sensitivity



Angular Sensitivity
(Relative Read Range vs. Orientation)



Angular Sensitivity
Inlay is rotated in the x, y, plane about the z axis
(tag shown at 0° with respect to face of antenna)

ALN-9627 “H” Inlay

ALN-9627 Specifications

Dry Inlay

Antenna Width	1.18" [30.0mm]
Antenna Length	1.77" [45.0 mm]
Web Width (FSR)	1.30" [33.0mm]
Web Pitch	2.00" [50.8mm]
Core Width (FSR)	1.30" [33.0mm]
Core ID	6" [152.4mm]
Core Material	Fiberboard
Interleaf Material	N/A
Interleaf Width	N/A
Inlays per Roll	8,000 Nominal
Maximum Roll OD	< 12" [304.8mm]
Roll Labeling Data	Roll #, Quantity

Wet Inlay

Inlay Width	1.5" [38.1mm]
Inlay Length	2.25" [57.15mm]
Web Width (FWRW)	1.625" [41.27 mm]
Web Pitch	2.375" [60.33]
Core Width	1.625" [41.27mm]
Core ID	3" [76.2mm]
Core Material	Fiberboard
Inlays per Roll	2,000 Nominal
Maximum Roll OD	< 16" [406.4mm]
Roll Labeling Data	Roll #, Quantity
White (-FWRW)	TT Printable Paper
Overlay Adhesive (-FWRW)	General Purpose Permanent
Inlay Adhesive	General Purpose Permanent
Adhesive Application Temperature	> +36.5°F [+2°C]
Adhesive Service Temperature	-4°F to +199.4°F [-20°C to +93°C]
Release Liner	40# SCK

Environmental

Shelf Life	2 Years at +77°F [+25°C] @ 40%RH
Recommended Storage	+77°F [+25°C] @ 40% RH -13°F to 122°F [-25°C to +50°C] 20% to 90% RH Non-condensing
Storage Limits	-40°F to +158°F [-40°C to +70°C] 20% to 90% RH Non-condensing
Operating Limits	
Bend Diameter	> 1.97" [50mm]
Pressure	< 5N/mm ²
Drop Resistance	Per ASTM D5276
Write Cycles	100,000 at 25°C
RoHs	2002/95/EC Compliant
ESD – HBM / CDM	> 5.0kV / > 1.5kV

RFID

ISO/IEC 18000-6C	
EPCglobal Class 1 Gen 2	
Integrated Circuit	Alien Higgs-3
EPCglobal Certificate	950110126000001084
Operating Frequency	840–960 MHz
EPC Size	96 - 480 Bits
User Memory	512 Bits
TID	32 Bits
Unique TID	64 Bits
Access Password	32 Bits
Kill Password	32 Bits



Copyright © 2011 Alien Technology Corporation

All rights reserved. Alien, Alien Technology, the Alien Technology logo, FSA™, Alien Higgs-3, Squiggle, and the Squiggle logo are trademarks or registered trademarks of Alien Technology Corporation in the U.S. and other countries.

HANDLING PRECAUTIONS Observe standard handling practices to minimize ESD.

DISCLAIMER Application recommendations are guidelines only - actual results may vary and should be confirmed. This is a general purpose product not designed or intended for any specific application.

Alien Technology
18220 Butterfield Blvd.
Morgan Hill, CA 95037
866-RFID NOW
www.alientechnology.com